



PUCKA-C

Order Code	DESCRIPTION
ED80-PUC-C-1W-A-W-12V	Input 12VDC, 1W CREE-XR-E-Q2 LED, cool white, 85LM
ED80-PUC-C-1W-A-WW-12V	Input 12VDC, 1W CREE-XR-E-P3 LED, warm white, 75LM
ED80-PUC-C-1W-B-W-12V	Input 12VDC, 1W high-lumen CREE-XR-E-Q5 LED, cool white, 120LM
ED80-PUC-C-1W-B-WW-12V	Input 12VDC, 1W high-lumen CREE-XR-E-P4 LED, warm white, 85LM

### Features

Lumen Output	Cree (1w) 70c/w 60w/w	Lumen Output	Cree (1w) 85-120 c/w 75-85w/w
Input Power	12 Volts	Voltage	12 Volts
Efficacy	74 lm/W	Color Temperature (CCT)	3500K to 6500K
Color Rendering Index (CRI)	75	Beam Spread	30 - 60 Degs
Rated Life	50,000 Hrs	LEDs	1 High Power 1W Cree Led
Housing	Brushed Aluminium	Mounting Options	Surface
Dimensions	33mm Dia x 21.5mm High	Power Supply	12 Volt Transformer
Warranty	2 Years	Environment	IP44
Wattage	Cree 1.2 Watts		

### Benefits

- Efficiency, Lifetime, and Safety,
- Maintenance free operation
- Energy efficient
- Long life 50,000 Hrs +
- Reliability

### Applications

- Architecture, ambience & decorative lighting
- Accent lighting
- Cove lighting
- Retail, corporate, public, residential
- Boat and Car Lighting

We reserve the right to make changes at any time in order to maintain the highest product quality.

The Fountain Business Park Ellis Street Coatbridge ML5 3AA  
Phone: 07540 479985 Email: sales@edenillumination.com

The Studio 55 Castle Terrace Leven Fife KY8 5EU  
Phone: 07905 565604 Email: sales@edenillumination.com

Web: [www.edenillumination.com](http://www.edenillumination.com)



PUCA-C REV-A SEP-2009